

## Installation Guide for TOPTEX® Fixing Tape

Securing your TOPTEX® cover properly prevents storm damage and ensures a high level of protection for the best straw and hay qualities.

### STEPS FOR TIGHTENING TOPTEX® WITH HANGING BALLAST

Correctly installed, hanging ballast ensures permanent tension for best protection.



#### 1 PREPARE FIXING TAPE

Cut fixing tape into 1 m pieces (15 m/roll = 15 pcs)




#### 2 PREPARE THE BAGS

Connect carabiner to fibre pocket of the bag or its handle




#### 3 PREPARE FULL FIXING KIT

Feed fixing tape through carabiner



#### 4 ATTACH THE TAPE AND BALLAST

Let the bag stand on the ground while holding the «V» shaped fixing tape in both hands, then lift and attach to the cover



#### 5 DETAILS FOR POSITIONING

Be aware that bales will settle over time

- Always place the ballast on a bale, never in the gap between two bales.
- Obey lifting height with 10-20cm distance between the bag and the ground.
- Avoid horizontal waves or folds on the surface of the cover.
- Lift and place the bag no higher than the center line of the bale. This will prevent pressure points on the bale.

#### 6 REPEAT THE PROCESS

The distance between the bags shall be 2 to 4 meters depending on the wind conditions; secure overlaps separately